

Series 4000H Automated Test System

The multifunction Series 4000H is a range of fully automated, computerized test systems that provide the highest level of specifications and features available in the industry.

From the base system that provides the highest level of accuracy and time resolution, features can be added to allow the Series 4000H system to perform virtually any type of test, with any type of products(i.e. batteries, super-capacitors, fuel cells, etc.) and chemistries.

Each test position

- Operates independently of the other positions
- Can be user programmed to run a wide range of multi step test, including pulse tests
- Can be user programmed to operate in steps of fixed current, fixed power, fixed voltage, fixed resistance, and voltage ramp(cyclic voltammetry)
- Can be set up to record data at operator specified intervals of time, voltage, current, etc.
- Is delivered calibrated to NIST traceable standards, and requires calibration only once per year.



TWO BAY SIZE Series 4000H

The Series 4000H systems are available in size from 1 to 192 test positions and are custom manufactured to meet a specific customer's requirements. They can be configured with a wide range of voltage and current ranges and can be fitted with optional hardware to provide a number of additional features and capabilities.

Based on tried and proven technology, the Series 4000H is designed to be readily upgradeable. This allows Maccor to continuously introduce new features that keep up with the ever-changing requirements and level of sophistication demanded by our customers.

Supplied as a complete turnkey system, the Series 4000H consists of a test cabinet, PC computer, tester software, and data analysis software. The test cabinet, with embedded microprocessors, and PC computer are connected via a 10 Base T LAN communications network.

To provide maximum reliability, flexibility, and speed of operation, embedded microprocessor controller boards provide control of the tests and collect data. Each controller supports from one to eight test channels, dependent on the application. In addition, the test cabinet contains the individually controlled programmable loads and power supplies.

Each test channel is operated independently. This allows different tests to be performed on different test channels simultaneously. Once started, tests operate automatically until the appropriately programmed test end condition is reached.

Tests are programmed, by the operator, on the host PC computer using a menu-driven build test program which is extremely user friendly and easy to use. When a test is started the test program is downloaded to the appropriate channel's embedded controller board. The controller board controls the test and collects the initial data measure by the programmable load. This measured data is then transferred to the PC computer for processing and storage.

The flexibility of the Series 4000H allows it to be used for a wide range of applications such as [Materials Research](#), [Portable Electronic Devices](#), [Quality Control in Manufacturing](#), [Research & Development](#), [Battery Pack Assembly](#), [Super-Capacitor Testing](#), [Fuel Cell Testing](#) [Thermal Battery Testing](#), [Qualification Testing](#), and [much more](#).

For battery testing, 4000H system can test any type of Primary and secondary battery((i.e. Alkaline, Ni-Cad battery, NI-MH battery, Lithium ion battery and Lithium polymer battery).

NOTE: SYSTEM CABINET TYPE AND IT'S COLOR ARE NOT ALWAYS IDENTICAL TO THE IMAGE SHOWN HEREOF .

Specifications

SERIES 4000H

Triple-Current Range

Current Range	Any combination of Triple-current ranges
Current Accuracy	$\pm 0.05\%$ Full Scale Range

Note: Triple current range is to be 1/10 of the highest current.

Ex: If customer want 200A as the highest range, then the second & third range are 20A & 2A

Voltage

Measurement Range	Per Your Specifications, voltages up to 180V available
Accuracy	$\pm 0.02\%$ Full Scale
Resolution	16 bit

Modes of Operation

Fixed(Constant) Current	Fixed(Constant) Power
Fixed(Constant) Resistance	Fixed(Constant) Voltage
1kHz AC Impedance Measurement(Under 20V channel)	
Voltage Ramp(Cyclic Voltammetry)	
Function	

Time

Minimum Step Time	10 mS‡
Control, Measurement, and Adjustment	every 10mS
‡ Optional 5mS and 1mS minimum step time available	

Options

Frequency Response Analyzer	Allows programming of AC amplitude for evaluating impedance spectroscopy of a device
Telecom Pulsing	GSM, CDMA, GPRS, Multi-Level, Multi-Slot, plus others
High-Speed Data Acquisition	Up to 1kHz in burst mode
Reference Electrode Inputs	High impedance, range $\pm 5V$
Thermocouple Inputs	Type "T", "K", or "J"
Thermistor Inputs	Various types
Pressure Inputs	Various ranges, for use with 0 to 100mV transducers
Auxiliary Voltage Inputs	$\pm 5V$, $\pm 10V$, $\pm 20V$, etc.
PH Inputs	Various ranges, for use with probes with $>10K$ input impedance
LED Status Indicators	Indicates active channel
External Charge Controllers	Rated from 5A to 200A, for use with external Battery chargers
External Load Controllers	Rated from 5A to 200A, for use with External loads
Smart Battery Packs	SMB communication for testing of smart battery packs
Environmental Chamber Control	Automatic control of supported environmental Chambers via RS232/485/IEE 488 interface
Cell Holders	Molded True 4-Wire Kelvin Cell Holders AAA, AA, C, D, 9V, and 18650 Adjustable Cylindrical Cell Holders Spring Loaded Binding Posts
Digital Inputs	For reading of TTL based inputs which can Control the flow of the test procedure
Digital Outputs	Allows for the setting of TTL based outputs which can be used to trigger an event or simply display status lights
Cables	Contact Maccor's Sales Department for Length and Terminations
Appropriately Sized Uninterruptible Power Supply	
Calibration and Maintenance Service	

AC Power Input

For each system, two separate AC inputs are required, one to power the electronics and one for the charge power.

Power for Electronics

110 or 220/240 VAC Single-Phase
or 380 three phase 50/60 Hertz

Power for Charge

186 to 256 VAC Single-Phase or
220 VAC or 380VAC Three-Phase
50/60 Hertz



Nono Tech System Co., Ltd

Gwanggyo Woomi NEWV A 913 & 914 (Sanghyeon Dong)
338, Gwanggyojungang-ro, Suji-gu, Yongin-si, Gyeonggi-do,
16942 Korea. TEL: 031-707-2002 FAX: 031-704-2007
<http://www.batterytestsystem.com>